


Anti-tracking certification for fiber optic cables



Anti-tracking certification for fiber optic cables



From copper twisted pair to high-speed fiber optics, we certify every cable run to industry standards. Category 5e, Cat6, Cat6A, and Cat8 testing with full TIA-568 compliance verification. Single-mode ...



Length:19.3mm
Small-end inner diameter:3.0mm
Large-end inner diameter:3.5mm
Outer diameter:5.5mm

Your source of certifications for fiber optic and copper connectivity products as well as company certifications.



Note 1: Please contact your sales agent for information about the total packaging dimensions and weight, as well as for higher fiber counts and different drum lengths available



Explore international standards and testing for fiber optic cables, MPO/MTP, and connectors. Understand performance, reliability, and compliance.



This specification covers the design requirements and performance standard for the supply of optical fibre cable in the industry. ARTIC ensures a stable quality control system for our products through ...



Stay compliant in 2025 with updated fiber testing standards for IEC and TIA. Learn key procedures, documentation tips, and legal requirements for your network.



Read all about our track-resistant ADSS Standard cable which can withstand long spans of 115 kV or greater on overhead lines, from our ADSS cable manufacturers.



Choose from various kits with configurations to meet your fiber verification, inspection, and cleaning needs.



As its name indicates, there is no support or messenger wire required, so installation is achieved in a single pass, making ADSS an economical and simple means of building a fiber optic network.

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://www.yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

