

# Distance of elevator electrical distribution box from the ground




## Overview

OSHA and the National Electrical Code (NEC) specify that electrical panels must have a minimum clearance of 36 inches in depth, 30 inches in width, and 78 inches in height. These dimensions ensure sufficient space for workers to safely and efficiently perform maintenance tasks. Electrical clearances set the minimum safe distances for panels, overhead lines, pools, and buried wiring — and ignoring them has real consequences. Dedicated space: The space equal to the width and depth of electrical equipment in addition to the space extending. For the safe operation and maintenance of equipment, access to and egress from working space must exist around all electrical equipment [110. Minimizing the need for. A few years later, in 1880, Werner von Siemens built the first electric elevator, setting the stage for a new industry that would change the world by making the practical use of tall buildings possible. For all of this to come together in the real world, there had to be some assurance that these. These requirements vary depending on whether the electrical equipment is rated at (1) 1,000 volts or less (See, Article #2) or (2) over 1,000 volts.

## Distance of elevator electrical distribution box from the ground



And though this aspect is not covered by the NEC [90.1], good engineering requires consideration of what additional distance would improve efficiency for operation or maintenance.



Minimum clearances are established for work spaces in front of high voltage - electrical equipment such as switchboards, control panels, switches, circuit breakers, switchgear and motor controllers. These ...



NEC Section 110.26 spells out three dimensions for this space. The working space must extend at least 36 inches deep, measured outward from the front of the panel. That 36-inch figure applies to ...



OSHA and the National Electrical Code (NEC) specify that electrical panels must have a minimum clearance of 36 inches in depth, 30 inches in width, and 78 inches in height. These dimensions ...



In many commercial facilities, electrical equipment rooms have rows of equipment operating at more than 150 volts to the ground. The aisle (s) between pieces of such equipment, with live parts on both ...



The intent of this manual is to clarify electric service requirements for Pacific Power and Rocky Mountain Power customers prior to and during construction. This manual may require different electrical ...



The basic requirement is for minimum clear distances of various depths for equipment operating at 600 V or less, nominal, depending upon voltage to ground and lateral distance to insulated or grounded ...



Where installed outdoors, the box shall be of weatherproof construction and mounted so that the bottom of the enclosure is not less than 152 mm (6 in.) above the ground;



Wiring related only to the elevator operation and equipment is permitted to be in these spaces, rooms, or hoistways. For example, some would purport that since machine room illumination ...



If electrical equipment is being replaced, Condition 2 working space is permitted between dead-front switchboards, switchgear, panelboards, or motor control centers located across the aisle from each ...

## Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://www.yoahorroenergia.es>

Email: [hello@yoahorroenergia.es](mailto:hello@yoahorroenergia.es)

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

