

# H3C locates access layer switches via IP address



## Overview

You can set an Ethernet port as a Layer 3 interface by using the port link-mode route command (see Layer 2—LAN Switching Configuration Guide). Use display ip interface to display IP configuration and statistics for the specified Layer 3 interface or all Layer 3. The IP addresses in this chapter refer to IPv4 addresses unless otherwise specified. com Software version: Release 2208 Document version: 6W100-20101224. All contents in this document, including statements, information, and recommendations, are believed to be accurate, but they are presented without warranty of any kind, express or implied. H3C shall not be liable for technical software features. Configure ip helper address in HP (H3C) switch. To enter in system-view mode use below: Author/Editor Founder of AAR TECHNOSOLUTIONS, Rashmi is an evangelist for IT and technology. Follow the commands below to create a user: Specify the user's access level. Below, this article will take the H3C simulator switch as an.

## H3C locates access layer switches via IP address




View and Download H3C S5120-EI Series configuration commands online. Layer 3 - IP Routing Command Reference. S5120-EI Series switch pdf manual download.



Find answers to Step by step configuration - HP H3C A5120 from the expert community at Experts Exchange



Configure ip helper address in HP (H3C) switch.



This connection method ensures that we can directly perform initial configuration on the switch, just like installing an "initial boot program" for the device, laying the foundation for subsequent ...



Use the display ip interface brief command to display brief IP configuration information, including the state, IP address, and description of the physical and link layer protocols, for the specified Layer 3 ...




Basic Command Configuration for H3C Switches. H3C switch commands bear resemblance to Huawei switch commands but with subtle differences. Let's first understand the ...



This article provides a hands-on guide to 50+ essential H3C switch commands, revealing hidden shortcuts and best practices derived from real-world ...



Learn how to create users, VLANs, enable Telnet and SSH, configure Spanning Tree Protocol, enable DHCP snooping, define trunk ports, and create access ports on H3C switches with step-by-step ...



Open the browser, enter in the address bar, and then press Enter. 192.168.0.233 is the default management IP address of the device, and you can edit the address after login.



This article provides a hands-on guide to 50+ essential H3C switch commands, revealing hidden shortcuts and best practices derived from real-world deployments in Fortune 500 data centers.

## Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://www.yoahorroenergia.es>

Email: [hello@yoahorroenergia.es](mailto:hello@yoahorroenergia.es)

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

