

Huawei Switch Optical Port Enable Configuration



Overview

To enable a port on a Huawei switch, start by accessing the device's command-line interface (CLI) via a console cable or SSH. Use the system-view command to enter configuration mode, then navigate to the target port using interface GigabitEthernet 0/0/1 (replace with your). This document describes all the configuration commands of the device, including the command function, syntax, parameters, views, default level, usage guidelines, examples, and related commands. Log in to the management interface using your username and password. For example: Replace VLAN_LIST with the VLANs allowed on the port. Loading. The Combo interface, also known as the optical-electrical multiplexing interface, consists of two Ethernet ports (one optical and one electrical) on the device panel, and there is only one forwarding interface inside the device. Issue 01 (2019-06-28) Copyright © Huawei Technologies Co. Run the display eth-trunk command to check the working mode of an.

Huawei Switch Optical Port Enable Configuration



☐☐ Learn how to fully configure a Huawei S5700 Series switch step-by-step using real CLI commands!



Execute the command “combo enable fiber” in interface mode to switch to the optical interface; on the contrary, “undo combo enable fiber” switches to the default electrical interface state.



The document provides configuration instructions and commands for basic switch configuration using Huawei switches. It covers topics such as changing the ...



This document discusses how to configure an Eth-Trunk in manual load balancing mode, how to configure an Eth-Trunk in LACP mode, and how to locate an Eth-Trunk fault.



Four SFP28 Ethernet optical interfaces (25GE by default) and two QSFP28 Ethernet optical interfaces (40GE by default) have been configured using the set device port-config-mode enable command.



This article summarizes several solutions for using optical modules with switches and common problems encountered during usage, along with specific solutions.



I will give an example of setting up ports on Huawei switches. For the test, I will execute commands on the Huawei Quidway S2326TP-EI. Loading...



The text covers tasks such as creating a user, VLAN configuration, port settings, enabling SSH and Telnet services, configuring Spanning Tree Protocol (STP), and other basic management operations ...



This guide dives into the step-by-step process of port configuration on Huawei switches, while addressing the often-overlooked question: Does opening ports inadvertently create backdoors ...



Both the local and remote interfaces do not need to have optical modules installed. The 40GE interface can be connected to four 10GE interfaces on the remote device using a 1-to-4 40GE ...

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://www.yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

