

Specifications for Adjustable Beam Attenuator



Specifications for Adjustable Beam Attenuator



The rear beam attenuator (RBA) provides automatically adjustable attenuation of the spectrophotometer's reference beam to extend its dynamic range and reduce noise at higher ...



Thorlabs' Beam Attenuators use a twofold reflection on two stacked prisms for attenuation of high-power beams up to 200 W (uncoated) or 50 W (AR coated). The ATT30 Series use a pair of UVFS prisms ...



After connecting the fiber, the distance between the fiber end face and the lens can be adjusted using the set screw, with a maximum adjustable travel of 5 mm. The attenuation level is controlled via a ...



Features
Divides laser beam into two beams of manually adjustable intensity ratio
Convenient 90° angle between reflected and transmitted beams
Negligible beam deviation
Large dynamic range ...



Using an attenuator the transmitted energy level within a laser beam delivery system is accurately controlled while the excimer laser maintains its optimum working point. Coherent follows a policy of ...

Contact Us

For more information, pricing, or custom data center solutions, please contact us:

Website: <https://www.yoahorroenergia.es>

Email: hello@yoahorroenergia.es

Phone: +233 54 318 7269

Address: Plot 28, Spintex Road, Accra, Greater Accra, Ghana

This document is for informational purposes only. Specifications subject to change without notice.

